(12) UK Patent Application (19) GB (11) 2 396 725

(43) Date of Printing by UK Office

30.06.2004

(21) Application No:

0406739.3

(22)Date of Filing: 26.09.2002

(30)Priority Data:

(31) 09967027

(32) 28.09.2001

(33) US

(86)International Application Data: PCT/US2002/030631 En 26.09.2002

International Publication Data: WO2003/036484 En 01.05.2003

(71) Applicant(s):

Chaparral Network Storage Inc 7420 East Dry Creek Parkway, Longmont, Colorado 80503, United States of America

(72) Inventor(s):

Victor Key Pecone

Agent and/or Address for Service:

W. H. Beck, Greener & Co 7 Stone Buildings, Lincoln's Inn, LONDON, WC2A 3SZ, United Kingdom

(51) INT CL7: G06F 13/00 11/16 13/40

UK CL (Edition W): (52)**G4A** AES AFGK AFGN

(56) Documents Cited by ISA:

US 6098140 A US 20020091828 A1 US 5483528 A US 20020029319 A1

(58)Field of Search by ISA:

Other: U.S.:710/100, 110,305,306;709/226;370/85.1

- Abstract Title: Bus zoning in a channel independent storage controller architecture
- A network storage controller for transferring data between a host computer and a storage device, such as a redundant array of inexpensive disks (RAID), is disclosed. The network storage controller includes at least one channel interface module which is adapted to be connected to the host computer and storage device. The channel interface module is connected to a passive backplane (112), and selectively transfers data between the host computer and storage device and the passive backplane. The network storage controller also includes at least one controller memory module (104), attached to the passive backplane. The controller memory module communicates with the channel interface module via the passive backplane, and processes and temporarily stores data received from the host computer or storage device. In applications where redundancy is required at least two controller memory modules and at least two channel interface modules are used. The controller memory modules may mirror data between one onother using the passive backplane and a shared communication path on the channel interface modules, thereby substantially avoiding the use of host or disk channels to mirror data. The channel interface modules are operable to selectively connect the host computer or storage device to one or more controller memory modules. The controller memory modules may include a DMA engine (188) to facilitate the transfer of mirrored data.

